

RO-IR UWB-06

TECHNICAL REGULATION

for the radio interface

concerning equipment using ultra-wideband (UWB) technology

(Location tracking systems type 1 (LT1))

98/34/EC Notification number: 2015/141/RO

1. Basic considerations

The Radio Equipment and Telecommunications Terminal Equipment Directive 1999/5/EC (R&TTE Directive) was implemented in Romania (RO) by Government Decision No. 130/2015.

This technical regulation contains the necessary equipment parameters for the licence exempt use of equipment using ultra-wideband (UWB) technology (Location tracking systems type 1 (LT1)) in the specified frequency bands and considers especially compliance with Articles 3.2, 4.1, 6 and 7.2 of Directive 1999/5/EC.

Nothing in this technical regulation shall preclude the need for equipment placed on the market in Romania to comply with Directive 1999/5/EC.

The obligations arising from Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations and of rules on Information Society services (OJ L 204 p. 37), as amended by Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 (OJ L 217 p. 18), have been hereby met.

All Romanian Technical Regulations notified under Directive 1998/34/EC will be published and will be made available free of charge from the ANCOM web-site at:

<http://www.ancom.org.ro/en/interface-regulations-2723>

2. Radio Interface Specifications

UWB location tracking systems type 1 (LT1)

Frequency range
$f \leq 1.6$ GHz
$1.6 < f \leq 2.7$ GHz
$2.7 < f \leq 3.4$ GHz
$3.4 < f \leq 3.8$ GHz
$3.8 < f \leq 6$ GHz
$6 < f \leq 8.5$ GHz
$8.5 < f \leq 9$ GHz
$9 < f \leq 10.6$ GHz
$f > 10.6$ GHz

For the purpose of this technical regulation, *equipment using ultra-wideband (UWB) technology* means equipment incorporating, as an integral part or as an accessory, technology for short-range radio communication, involving the intentional generation and transmission of radio-frequency energy that spreads over a frequency range wider than 50 MHz, which may overlap several frequency bands allocated to radio communication services.

LT1 are systems intended for general location tracking of people and objects that can be put into service on an unlicensed basis.

Maximum mean power spectral density, specified as e.i.r.p. of the radio device under test at a particular frequency, is the average power per unit bandwidth (centred on that frequency) radiated in the direction of the maximum level under the specified conditions of measurement.

Peak power, specified as e.i.r.p., is the power contained within a 50 MHz bandwidth at the frequency at which the highest mean radiated power occurs, radiated in the direction of the maximum level under the specified conditions of measurement.

For the purpose of this technical regulation, *non-interference and non-protected basis* means that no harmful interference may be caused to any radio communications service and that no claim may be made for protection of these devices against harmful interference originating from radio communications services.

The use of radio spectrum by equipment using ultra-wideband technology (UWB) is allowed on a non-interference and non-protected basis provided that such equipment meets the conditions set out in the Annex and it is used indoors or, if it is used outdoors, it is not attached to a fixed installation, a fixed infrastructure or a fixed outdoor antenna.

ROMANIA	Radio Interface Specification	SRD / UWB applications	RO-IR UWB-06	Edition 1/ 2015
---------	-------------------------------	------------------------	--------------	-----------------

	Nr	Parameter	Description	Comments																														
Normative part	1	Radio communication Service																																
	2	Application	Short Range Devices / UWB applications	Location tracking systems type 1 (LT1)																														
	3	Frequency band	See row (7) below for applicable frequency bands	Harmonised radio spectrum for ultra-wideband technology (Decision 2014/702/EU amending Decision 2007/131/EC)																														
	4	Channelling	-																															
	5	Modulation / Occupied bandwidth	-																															
	6	Direction / Separation	-																															
	7	Transmit power / Power density	<table border="1"> <thead> <tr> <th>Frequency range</th> <th>Maximum mean power spectral density (e.i.r.p)</th> <th>Maximum peak power (e.i.r.p) (defined in 50 MHz)</th> </tr> </thead> <tbody> <tr> <td>$f \leq 1.6$ GHz</td> <td>- 90 dBm/MHz</td> <td>- 50 dBm</td> </tr> <tr> <td>$1.6 < f \leq 2.7$ GHz</td> <td>- 85 dBm/MHz</td> <td>- 45 dBm</td> </tr> <tr> <td>$2.7 < f \leq 3.4$ GHz</td> <td>- 70 dBm/MHz</td> <td>- 36 dBm</td> </tr> <tr> <td>$3.4 < f \leq 3.8$ GHz</td> <td>- 80 dBm/MHz</td> <td>- 40 dBm</td> </tr> <tr> <td>$3.8 < f \leq 6$ GHz</td> <td>- 70 dBm/MHz</td> <td>- 30 dBm</td> </tr> <tr> <td>$6 < f \leq 8.5$ GHz</td> <td>- 41.3 dBm/MHz</td> <td>0 dBm</td> </tr> <tr> <td>$8.5 < f \leq 9$ GHz</td> <td>- 65 dBm/MHz or - 41.3 dBm/MHz using DAA ⁽¹⁾</td> <td>- 25 dBm or 0 dBm</td> </tr> <tr> <td>$9 < f \leq 10.6$ GHz</td> <td>- 65 dBm/MHz</td> <td>- 25 dBm</td> </tr> <tr> <td>$f > 10.6$ GHz</td> <td>- 85 dBm/MHz</td> <td>- 45 dBm</td> </tr> </tbody> </table>	Frequency range	Maximum mean power spectral density (e.i.r.p)	Maximum peak power (e.i.r.p) (defined in 50 MHz)	$f \leq 1.6$ GHz	- 90 dBm/MHz	- 50 dBm	$1.6 < f \leq 2.7$ GHz	- 85 dBm/MHz	- 45 dBm	$2.7 < f \leq 3.4$ GHz	- 70 dBm/MHz	- 36 dBm	$3.4 < f \leq 3.8$ GHz	- 80 dBm/MHz	- 40 dBm	$3.8 < f \leq 6$ GHz	- 70 dBm/MHz	- 30 dBm	$6 < f \leq 8.5$ GHz	- 41.3 dBm/MHz	0 dBm	$8.5 < f \leq 9$ GHz	- 65 dBm/MHz or - 41.3 dBm/MHz using DAA ⁽¹⁾	- 25 dBm or 0 dBm	$9 < f \leq 10.6$ GHz	- 65 dBm/MHz	- 25 dBm	$f > 10.6$ GHz	- 85 dBm/MHz	- 45 dBm	
	Frequency range	Maximum mean power spectral density (e.i.r.p)	Maximum peak power (e.i.r.p) (defined in 50 MHz)																															
	$f \leq 1.6$ GHz	- 90 dBm/MHz	- 50 dBm																															
	$1.6 < f \leq 2.7$ GHz	- 85 dBm/MHz	- 45 dBm																															
	$2.7 < f \leq 3.4$ GHz	- 70 dBm/MHz	- 36 dBm																															
$3.4 < f \leq 3.8$ GHz	- 80 dBm/MHz	- 40 dBm																																
$3.8 < f \leq 6$ GHz	- 70 dBm/MHz	- 30 dBm																																
$6 < f \leq 8.5$ GHz	- 41.3 dBm/MHz	0 dBm																																
$8.5 < f \leq 9$ GHz	- 65 dBm/MHz or - 41.3 dBm/MHz using DAA ⁽¹⁾	- 25 dBm or 0 dBm																																
$9 < f \leq 10.6$ GHz	- 65 dBm/MHz	- 25 dBm																																
$f > 10.6$ GHz	- 85 dBm/MHz	- 45 dBm																																
8	Channel access and occupation rules	-																																
9	Authorisation regime	Licence exemption																																
10	Additional essential requirements	-																																
11	Frequency planning assumptions	-																																

Informative part	12	Planned changes	-	
	13	Reference	Decision 2014/702/EU amending Decision 2007/131/EC; EN 302 065	
	14	Notification number	2015/141/RO	
	15	Remarks	<i>(¹) The Detect and Avoid (DAA) mitigation technique and its limits are defined in ETSI Standard EN 302 065-2.</i>	